

# #07



100% DESIGNED  
AND PRODUCED  
IN BELGIUM

## TECHNICAL SPECIFICATIONS

### PRODUCT INFORMATION

Productnorm	EN 16511	
Level of use	EN ISO 10874	23 - 32
Total thickness	EN ISO 24346	4+1 mm
Wear layer PUR treatment		Superguard Prime®
Total weight g/m <sup>2</sup>	EN ISO 23997	6,650 g/m <sup>2</sup>

### SIZE & PACKING

Planks	EN ISO 24342	18,9 x 125,1 cm
Box planks	9 pcs/box	2,128 m <sup>2</sup> /box

### TEST RESULTS

Inflammability	EN 13501-1	Bfl-s1
Squareness & straightness	EN ISO 24342	≤ 400 mm: ≤ 0,25 mm   > 400 mm: ≤ 0,35 mm
Slip resistance	EN 13893	DS
Slip restraint	EN 16165:2021-10 Annex B	≥9
Residual indentation	EN 24343-1	≤ 0,2 mm
Furniture leg resistance	EN 424	No cracks, no damage
Curling	EN ISO 23999	≤ 111 mm
Electrical resistance	EN 1081	≤ 10 <sup>9</sup> Ohm
Dimensional stability	EN ISO 23999	≤ 0,25 %
Thermal resistance R	EN 12667	0,033 m <sup>2</sup> .K/W
Formaldehyde group	EN 717-1	E1
Acoustic insulation	EN 10140-1/3	Δ Lw ≥ 19 dB
Castor chair resistance	EN 425	No damage to wearlayer, no delamination
Stain resistance	EN 438-2	Very good
Light fastness	ISO 105-B02:2014	≥ 6
Underfloor heating		Suitable, max 27°C
Warranty (year)		15 Residential   5 Commercial

The warranty covers manufacturing defects and premature wear in the event of normal use.



**CE**  
EN 14041:2004 / AC:2006  
Multilayer Modular Floorcoverings  
EN 16511:2014



**UNICLIC**®  
PATENTED TECHNOLOGY